

SALES FACT SHEET

FO*15R SERIES

Efficiencies: 14 to 15 SEER/
11.5 to 12.5 EER

Nominal Sizes 1.5 to 5 Ton

[5.28 to 17.6 kW]

Cooling Capacities 17.3 to 60.5 kBTU
[5.7 to 17.7 kW]



GENERAL TERMS OF LIMITED WARRANTY*

Fujitsu General America, Inc. will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty. Conditional Parts
(Registration Required)Ten (10) Years

*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.


15 SEER Heat Pumps

Features:

- New composite base pan – dampens sound, captures louver panels, eliminates corrosion and reduces number of fasteners needed
- Improved tubing design – reduces vibration and stress, making unit quieter and reducing opportunity for leaks
- Optimized defrost characteristics - decrease defrosting and provide better home comfort
- Powder coat paint system – for a long lasting professional finish
- Optimized reversing valve sizing – improves shifting performance for quieter unit operation and increased life of the system
- Enhanced mufflers – help to dissipate vibration energy for quieter unit operation
- Scroll compressor – a sound abating feature added to the compressor significantly reduces noise when system transitions in and out of defrost mode
- Modern cabinet aesthetics – increased curb appeal with visually appealing design
- Curved louver panels – provide ultimate coil protection, enhance cabinet strength, and increased cabinet rigidity
- Optimized fan orifice – optimizes airflow and reduces unit sound
- Rust resistant screws – confirmed through 1500-hour salt spray testing
- Service valve has between 3"-4"-5" service valve space – provides a minimum working area of 27-square inches for easier access
- Integrated heat pump lift receptacle – allows standard CPVC stands to be inserted into the base
- 15" wide, industry leading corner service access – makes repairs easier and faster.
- External gauge port access – allows easy connection of "low-loss" gauge ports
- Single-row condenser coil – makes unit lighter and allows thorough coil cleaning to maintain "out of the box" performance
- Fewer cabinet fasteners and fastener-free base – allow for faster access to internal components and hassle-free panel removal
- Service trays – hold fasteners or caps during service calls
- QR code – provides technical information on demand for faster service calls
- Fan motor harness with extra-long wires – allows unit top to be removed without disconnecting fan wire

| Model FO*15R | Nominal Cooling Capacity | Voltage | Phase | OPERATING | | | Service Valve - Liquid | Service Valve - Suction | Shipping Lbs. [kg] | Price |
|-----------------|--------------------------------|---------|-------|---------------------------|---------------------------|--------------------------|------------------------------|-------------------------------|-----------------------|-------|
| | | | | Height "H" Inches [mm] | Length "L" Inches [mm] | Width "W" Inches [mm] | | | | |
| 18 | 18,000 | 208/230 | 1 | 25 [635] | 29.75 [755] | 29.75 [755] | 3/8" | 3/4" | 156 [70.7] | |
| 24 | 24,000 | 208/230 | 1 | 25 [635] | 29.75 [755] | 29.75 [755] | 3/8" | 3/4" | 159 [72.1] | |
| 30 | 30,000 | 208/230 | 1 | 31 [787] | 33.75 [857] | 33.75 [857] | 3/8" | 3/4" | 167 [75.8] | |
| 36 | 36,000 | 208/230 | 1 | 35 [889] | 33.75 [857] | 33.75 [857] | 3/8" | 3/4" | 179 [81.2] | |
| | | 208/230 | 3 | | | | | | | |
| | | 460 | 3 | | | | | | | |
| 42 | 42,000 | 208/230 | 1 | 35 [889] | 33.75 [857] | 33.75 [857] | 3/8" | 7/8" | 187 [84.8] | |
| | | 208/230 | 3 | | | | | | | |
| | | 460 | 3 | | | | | | | |
| 48 | 48,000 | 208/230 | 1 | 39 [991] | 35.75 [908] | 35.75 [908] | 3/8" | 7/8" | 215 [97.5] | |
| | | 208/230 | 3 | | | | | | | |
| | | 460 | 3 | | | | | | | |
| 60 | 60,000 | 208/230 | 1 | 45 [1143] | 35.75 [908] | 35.75 [908] | 3/8" | 7/8" | 243 [110.2] | |
| | | 208/230 | 3 | | | | | | | |
| | | 460 | 3 | | | | | | | |

[] Designates Metric Conversions





SALES FACT SHEET

| ACCESSORIES | | |
|---|-------------|-------|
| Description | Part No. | Price |
| Low Ambient Control (RXAD-A08) | RXAD-A08 | |
| Crankcase Heater for 1.5 - 3 ton Models | 44-17402-44 | |
| Crankcase Heater for 3.5 - 5 ton Models | 44-17402-45 | |
| Low Pressure Control | RXAC-A07 | |
| High Pressure Control | RXAB-A07 | |
| Compressor Sound Cover 1.5 - 3 ton Models | 68-23427-26 | |
| Compressor Sound Cover 3.5 - 5 ton Models | 68-23427-25 | |
| Compressor Hard Start Kit | SK-A1 | |
| Heat Pump Riser | 686020 | |

Total Price

\$