

**10 Ton Heat Recovery Outdoor Unit - 208/230 VAC, 3-Phase, 60Hz
1X (AOUA120TLBV)**

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

- Inverter driven compressor
- New style high power DC fan motor.
- Blue fin heat-exchanger (Corrosion resistance)
- 10 year Extended Warranty on parts and compressor. See Warranty Statement.
- Optional: Internet, BACnet, LonWorks, or Modbus communication.



CAPACITY	
Nominal Cooling Capacity - BTU/h [kW]	120,000 [35.2]
Nominal Heating Capacity - BTU/h [kW]	135,000 [39.6]
Nominal Tonnage - Ton(s)	10
Maximum Connectable Indoor Units	18
Connectable Capacity	50% to 150%
Cooling Power Input - kW	9.75
Heating Power Input - kW	10.11
Unit Group	1X (AOUA120TLBV)

OPERATING TEMPERATURES	
Operating Temp. Cooling (DB) - °F [°C]	14 to 115 [-10 to 46]
Operating Temp. Heating (DB) - °F [°C]	-4 to 70 [-20 to 21]
Operating Temp. Cooling/Heating Simultaneous - °F [°C]	14 to 70 [-10 to 21]

ELECTRICAL	
Electrical Power Requirements	208/230 VAC, 3-Phase, 60Hz
Voltage Range	187 to 253 VAC
Maximum Circuit Breaker - A	60
Minimum Circuit Ampacity (MCA) - A	50
Cooling Power Input - kW	9.75
Heating Power Input - kW	10.11
Maximum Starting Current (MSC) - A	40
Compressor - Rated Load Amperage (RLA) - A	32
Fan Motor - Full Load Amperage (FLA) - A	3.4

EFFICIENCY	
EER Cooling (Ducted/Non Ducted)	11.30/11.30
IEER Cooling (Ducted/Non Ducted)	23.80/20.10
COP / High Heating 47°F (Ducted/Non Ducted)	3.61/3.49
SCHE (Ducted/Non Ducted)	25.40/25.80

COMPRESSOR	
Compressor Type	Rotary Inverter
Refrigerant Type	R410A
Refrigerant Charge - lbs [kg]	26.01 [11.80]
Compressor Crankcase Heater - W	2X 35
Refrigerant Oil / Lubricant	POE
Compressor Capacity Control - Steps/Range	951 / 20 - 115

WIRING	
Communication Cable	LonWorks (Fujitsu Pink Cable. See AE Bulletin 009)

FAN	
Fan Type	Propeller fan
Fan Airflow Rate - CFM [m3/h]	7,652 [13,000]
Fan Power Output - W	740
Fan Motor - Full Load Amperage (FLA) - A	3.4
External Static Pressure (Max) - in.WG [Pa]	0.32 [80]

PIPING	
Max. Total Refrigerant Line Length - ft [m]	3,280 [1,000]
Max Height Diff. (OD & ID) (Upper/Lower) - ft [m]	164/131 [50/40]
Max. Refrig. Line Length 1st Sep. tube & furthest IU - ft [m]	196 [60]
Pipe Connection Method: Liquid/Gas	Brazed
Pipe Connection: Liquid - in [mm]	1/2 [12.70]
Pipe Connection: Discharge Gas - in [mm]	3/4 [19.05]
Pipe Connection: Suction Gas - in [mm]	1-1/8 [28.58]

HEAT EXCHANGER	
H. E. Pipe Type (Material)	Grooved H-pin (Copper)
H. E. Fin Tube (Material)	Corrugate (Aluminum)
H. E. Fin Surface Treatment	Corrosion resistance (Blue fin)
H. E. Fin Pitch - FPI [mm]	18 [1.45]
H. E. Rows x Stages	3 x 60
H. E. Face Area - Ft ² [m ²]	28 [2.6]
H. E. Length - in [mm]	81-1/2 (2070)

SOUND	
Sound Pressure Levels (Cooling/Heating) - dB(A)	61/62

WEIGHT	
Net Weight - lbs [kg]	639 [290]
Gross Weight - lbs [kg]	690 [313]

DIMENSIONS	
Dim.Net (HxWxD) - in [mm]	66-9/16 × 48-13/16 × 30-1/8 [1690 × 1240 × 765]

Dim.Gross (HxWxD) - in [mm]	71-5/16 × 51-5/8 × 33-3/8 [1811 × 1312 × 847]
-----------------------------	--

CODE	
ETL	3170288
AHRI Certified	Standard 1230

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).



Fujitsu General America, Inc.
 353 Route 46 West
 Fairfield, NJ 07004
 Toll Free: (888) 888-3424
 Fax: (973) 836-0453
 www.airstagevrf.com

DIMENSIONS

Unit: In. (mm)

