

Inverter Driven Heat Pump

9,000 BTU Single Zone Compact Cassette

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

- 24 hr. Timer/Weekly Timer
- Auto louver: Up/Down
- Auto Mode
- Auto Changeover
- Daisy Chain Compatible
- Built-in Condensate Pump
- Auto Restart
- Economy Mode
- Auto Fan Mode



MODEL NUMBERS

Indoor Unit	AU9RLF
Outdoor Unit	AOU9RFCC
System	9RL FCC

EFFICIENCIES

SEER	24
EER	14.5
HSPF	13
COP	3.95
	13.50

OUTDOOR TEMPERATURE OPERATION RANGE

Cooling	*F(°C)	14 to 115 (-10 to 46)
Heating		-5 to 75 (-21 to 24)

CAPACITIES

Cooling	Rated	BTU/hW	9,000
	Min.-Max.		3100 - 12000
Heating	Rated		12,000
	Min.-Max.		3100 - 18000

LINESET REQUIREMENTS

Connection Method	Flare		
Liquid	in (mm)	Ø1/4 (Ø6.35)	
Gas		Ø3/8 (Ø9.52)	
Pre-Charge Length	ft (m)	49 (15)	
Minimum Length		10 (3)	
Maximum Length		66 (20)	
Max. Height Diff.		49 (15)	

INDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	9-21/32 x 22-7/16 x 22-7/16
	mm	(245x570x570)
Gross (H x W x D)	in	10-7/16 x 28-3/4 x 24-19/32
	mm	(265x730x625)
Net Weight	lb (kg)	33 (15)
Gross Weight		40 (18)

OUTDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	24-1/2 x 31-3/32 x 11-11/32
	mm	(620 x 790 x 290)
Gross (H x W x D)	in	28-1/16 x 37-7/32 x 15-9/16
	mm	(713 x 945 x 395)
Net Weight	lb (kg)	84 (38)
Gross Weight		93 (42)



Indoor Unit ETL#: 3170288
 Outdoor Unit ETL#: 91987

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-TTRX	3rd Party Thermostat Converter
UTY-RNNUM	Wired Remote
UTY-RVNUM	Wired Remote w/backlight
UTY-RSNUM	Simple Remote
UTY-XWZX	Dry Contact Wire Kit
FJ-IR-WIFI-1NA	Intesis IR WiFi module
FJ-RC-WIFI-1NA	Intesis Wired WiFi module
UTY-TFNXZ2	WiFi interface Module
UTZ-VXAA	Fresh Air intake



This system combination is Energy Star qualified

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://portal.fujitsugeneral.com>

Inverter Driven Heat Pump 9,000 BTU Single Zone Compact Cassette

FAN DATA

Indoor Unit Airflow Rate	Cooling	High	CFM (m3/h)	318 (540)
		Medium		288 (490)
		Low		259 (440)
		Quiet		230 (390)
	Heating	High		318 (540)
		Medium		288 (490)
		Low		259 (440)
		Quiet		230 (390)
Outdoor Unit Airflow Rate	Cooling		795 (1,350)	
	Heating		989 (1,680)	

SOUND PRESSURE

Indoor Unit	Cooling	High	dB (A)	33
		Medium		32
		Low		29
		Quiet		28
	Heating	High		34
		Medium		32
		Low		29
		Quiet		27
Outdoor Unit	Cooling		44	
	Heating		49	

REFRIGERANT

Type	R410A		
Charge	lb oz	2 lb 10 oz	
	kg	1,200	
Oil Type	FREOL α68SZ		

ELECTRICAL SPECIFICATIONS


Voltage/Frequency/Phase				208 / 230V ~ 60Hz
Voltage Range				107 ~ 233V
Current	Cooling	Rated	A	3.0
	Heating	Rated		4.1
Maximum Operating Current	Cooling			9.3
	Heating			10.8
Starting Current				4.1
MCA				13.4
Maximum Circuit Breaker				15
Input Power	Cooling	Rated	kW	0.62
		Min.-Max.		1.4
	Heating	Rated		0.89
Power Factor	Cooling		%	90
	Heating		%	94

OTHER

Moisture Removal	pints/h (L/h)	(1.3) 0.6	
Energy Star		Yes	
Drain hose	Material	Hard PVC	
Size	in (mm)	Ø1/2 (Ø13.0) [I.D.], Ø5/8 to Ø11/16 (Ø16.0 to Ø16.7) [O.D.]	
	Operation Range		
Range	Cooling	°F (°C)	64 to 90 (18 to 32)
		%RH	80 or less
	Heating	°F (°C)	60 to 88 (16 to 30)

GRILL DATA

- Grid type grille (UTG-CCGFG)




The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).

Inverter Driven Heat Pump 9,000 BTU Single Zone Compact Cassette

DIMENSIONS

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2018 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m). Height difference: 0ft. (0m) (Outdoor unit - indoor unit).